

**Declaration Owner**

Sloan Valve Company
10500 Seymour Avenue, Franklin Park, IL 60131
P: 847.671.4300 / 800.982.5839 · www.sloan.com

Product

Basys® EFX Sensor Faucets

Functional Unit

Sensor faucets are intended for use in public lavatories as the dispensing unit for the water supplied, primarily for hand washing or simple rinsing. These fixtures are primarily installed in the commercial environment including commercial buildings, airports, stadiums, healthcare, hospitality sectors, etc. The functional unit is defined as "10 years of use of a faucet in an average US public lavatory environment". The lifespan of 10 years is an industry accepted average lifetime that is based on the economic lifespan of a product. However, the faucet lifespan may well greatly exceed 10 years with proper maintenance.

The scope of this EPD is Cradle-to-Grave.

EPD Number and Period of Validity

SCS-EPD-05194
EPD Valid October 24, 2018 through October 23, 2023
Version: May 7, 2019

Product Category Rule



Part A: LCA Calculation Rules and Report Requirements v2018; Sustainable Minds (March 2018).

Part B: Product Group Definition | Public Lavatory Faucets; Sustainable Minds (July 3, 2018).

Program Operator

SCS Global Services
2000 Powell Street, Ste. 600, Emeryville, CA 94608
+1.510.452.8000 | www.SCSglobalServices.com



Declaration Owner:	Sloan Valve Company
Address:	10500 Seymour Avenue, Franklin Park, IL 60131
Declaration Number:	SCS-EPD-05194
Declaration Validity Period:	EPD Valid October 24, 2018 through October 23, 2023
Version Date:	May 7, 2019
Program Operator:	SCS Global Services
Declaration URL Link:	https://www.scsglobalservices.com/certified-green-products-guide
LCA Practitioner:	Aditi Suresh, SCS Global Services
LCA Software:	SimaPro v8.3
Independent critical review of the LCA and data, according to ISO 14044 and ISO 14071	<input type="checkbox"/> internal <input checked="" type="checkbox"/> external
LCA Reviewer:	 Tom Gloria, Ph.D. Industrial Ecology Consultants
Part A Product Category Rule:	LCA Calculation Rules and Report Requirements v2018; Sustainable Minds (March 2018).
Part A PCR Review conducted by:	Part A PCR review conducted by the SM TAB, tab@sustainableminds.com
Part B Product Category Rule:	Product Group Definition Product Group Definition Public Lavatory Faucets; Sustainable Minds (July 3, 2018).
Part B PCR Review conducted by:	Part B PCR review conducted by the SM TAB, tab@sustainableminds.com
Independent verification of the declaration and data, according to ISO 14025 and the PCR	<input type="checkbox"/> internal <input checked="" type="checkbox"/> external
EPD Verifier:	 Tom Gloria, Ph.D., Industrial Ecology Consultants
Declaration Contents:	Product and Company Information.....cover Product2 Product Description.....2 Material Resources.....2 Additional Environmental Information.....2 Life Cycle Assessment Overview.....2 Process Flow Diagram.....4 Life Cycle Impact Assessment.....5 Additional Environmental Parameters.....6 Supporting Technical Information.....9 References.....11
<p>Disclaimers: This EPD conforms to ISO 14025, 14040, 14044, and ISO 21930.</p> <p>Scope of Results Reported: The PCR requirements limit the scope of the LCA metrics such that the results exclude environmental and social performance benchmarks and thresholds, and exclude impacts from the depletion of natural resources, land use ecological impacts, ocean impacts related to greenhouse gas emissions, risks from hazardous wastes and impacts linked to hazardous chemical emissions.</p> <p>Accuracy of Results: Due to PCR constraints, this EPD provides estimations of potential impacts that are inherently limited in terms of accuracy.</p> <p>Comparability: The PCR this EPD was based on was not written to support comparative assertions. EPDs based on different PCRs, or different calculation models, may not be comparable. When attempting to compare EPDs or life cycle impacts of products from different companies, the user should be aware of the uncertainty in the final results, due to and not limited to, the practitioner's assumptions, the source of the data used in the study, and the specifics of the product modeled.</p>	

PRODUCT

The following sensor faucets are represented by this EPD:

Basys® EFX Sensor Faucets			
Model #	Flow Rate	Model #	Flow Rate
EFX200	(0.5 gpm/1.9 lpm)	EFX277	(0.5 gpm/1.9 lpm)
EFX250	(0.5 gpm/1.9 lpm)	EFX280	(0.5 gpm/1.9 lpm)
EFX275	(0.5 gpm/1.9 lpm)		

PRODUCT DESCRIPTION

Sensor-activated faucets are designed to deliver a preset volume of water into a lavatory. Sloan's line of Basys® faucets have a reputation for reliability and proven engineering expertise and a wide range of design and feature options. Easy, above-deck access to key components is the standard for all BASYS models. The on-board electronics are completely sealed within each faucet's modular crown, which can be removed with a single Allen wrench. This line of hygienic, touch-free electronic operation faucets are vandal resistant that stand up to the harshest commercial environments



BASYS® Solar Powered Deck-Mounted Mid Body Faucet



BASYS® Battery Powered Deck-Mounted Mid Body Faucet

The EFX 277 Basys® faucet is Solar-Powered Deck-Mounted Mid Body Faucet with 0.5 gpm/1.9 Lpm flow rate and features an integrated side mixer, multi-laminar spray. Basys® EFX sensor faucets meet the following certifications: Americans with Disabilities Act (ADA), California Energy Commission (CEC), CalGreen Code, LEED v4 (with 0.35 gpm spray option) These sensor faucets are available with the following features:

- One tool service
- All wetted components to be stainless steel, engineered thermoplastic, EPDM, and copper or copper alloy
- Solenoid housed in removable carrier that includes supply strainer
- Integral water supply shut off
- Supply strainer serviceable from above deck
- Vandal resistant spray insert, key housed inside faucet body
- All electronics sealed to IP-224
- Gold plated electrical contacts
- Above deck individual diagnostic indicators for battery life, solenoid condition, and power up mode
- Flexible, high pressure supply hoses, 3/8" compression connections
- Bi-stable magnetic solenoid
- Four power options are available, giving you the flexibility to best meet your specific application needs: Battery, Solar, Hardwired with Battery Backup and turbine.
- Double infrared sensors with automatic setting feature Includes all mounting hardware

MATERIAL RESOURCES

The material composition and availability of raw material resources of the Basys® EFX sensor faucets are shown in Table 1. Information on product packaging is shown in Table 2.

Table 1. Material composition (in % of mass) of Basys® EFX sensor faucets.

Material	% Mass	Availability			
		Renewable	Non-Renewable	Pre-Consumer Recycled Content	Post-Consumer Recycled Content
Zamak	33%		Yes	0%	0%
Brass	19%		Yes	20%	0%
Sensor	12%		Yes	0%	0%
Stainless Steel	12%		Yes	15%	0%
Battery	8.3%		Yes	0%	0%
Polyphthalamide (PPA)- 40% glass filled	6.0%		Yes	0%	0%
Copper	5.1%		Yes	0%	0%
Nylon 6-glass filled	1.7%		Yes	0%	0%
EPDM	0.97%		Yes	0%	0%
PVC	0.67%		Yes	0%	0%
Acetal	0.60%		Yes	0%	0%
Solar Cell	0.58%		Yes	0%	0%
Polypropylene	0.09%		Yes	0%	0%
Polyamide plastic	0.05%		Yes	0%	0%
LDPE	0.03%		Yes	0%	0%
ABS	0.02%		Yes	0%	0%
Magnet	0.004%		Yes	0%	0%
Rubber	0.002%	Yes		0%	0%
Adhesive	0.001%		Yes	0%	0%
TOTAL	100%				

Table 2. Material composition (in % of mass) of packaging for Basys® EFX sensor faucets.

Material	% Mass	Availability			
		Renewable	Non-Renewable	Pre-Consumer Recycled Content	Post-Consumer Recycled Content
Cardboard	89%	Yes		3%	5%
Paper	0.90%	Yes		0%	0%
LDPE film	10%		Yes	0%	0%
Plastic label	0.14%		Yes	0%	0%
TOTAL	100%				

ADDITIONAL ENVIRONMENTAL INFORMATION

Sloan is a proud member of the United States Green Building Council (USGBC) and through the use of the Leadership in Energy and Environmental Design (LEED) Green Building Rating System, Sloan recognizes and validates the importance of best-in-class building strategies and practices of high performing green buildings. Sloan’s Basys® EFX faucets within this EPD can be used to help achieve water efficiency goals as well as gaining USGBC LEED v4 points and/or complying with CAL Green and other building code requirements.

LIFE CYCLE ASSESSMENT OVERVIEW

The system boundary is cradle-to-grave and includes resource extraction and processing, product manufacture and assembly, distribution/transport, use and maintenance, and end-of-life. The diagram below illustrates the life cycle stages included in this EPD.

Product			Construction Process		Use							End-of-Life				Benefits & Loads Beyond the System Boundary
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Raw Material Extraction and Processing	Transport to the Manufacturer	Manufacturing	Transport	Construction - Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction demolition	Transport	Waste processing	Disposal	Reuse, recovery, and/or recycling potential
X	X	X	X	X	NR	X	X	NR	NR	NR	X	X	X	X	X	MND

X = Included, MND = module not declared, NR = not relevant

The following provides a brief overview of the Modules included in the product system for Basys® EFX sensor faucets.

Module A1 Raw material extraction and processing, processing of secondary material inputs for sensor faucets

This module includes the potential environmental impacts associated with the extraction and processing of raw materials for various component parts in the sensor faucet. The zamak and brass components are one of the primary materials, comprising of 33% and 19%, respectively of the sensor faucet product composition.

Module A2: Transportation

This module includes the transportation of all raw material components (such as brass, plastics, stainless steel, synthetic rubber, etc.) from the suppliers to the Swiss facility.

Module A3: Manufacture of Sensor faucet

This module includes the manufacturing, assembly and packaging of the final sensor faucet at the Swiss facility.

Module A4: Transportation & Delivery to the site

This module includes the impacts associated with transportation of finished sensor faucets to the U.S. based distribution center and the subsequent delivery to the installation site.

Module A5: Construction & Installation

The installation of sensor faucets is performed with hand tools and does not require any ancillary material input. This module considers the impacts associated with waste processing and disposal of product packaging waste generated during the installation process.

Module B1: Normal use of the product

This module includes environmental impacts arising through normal anticipated use of the product. This module is not applicable because the anticipated use of the faucet is accounted for in Module B7: Operational water use.

Module B2: Maintenance

This module considers the impacts associated with cleaning and maintenance of the product over a 10-year period. Cleaning of the faucet is assumed to occur daily using 10ml of 1% sodium lauryl sulfate solution. The faucets are cleaned daily for a period of 10 years, corresponding to the functional unit for the assessment. Additionally, waste processing and disposal related to these maintenance activities are included in this module.

Module B3: Repair

This module includes any anticipated repair events during the reference service of the faucets. Based on the manufacturer's recommendation, alkaline batteries of the sensor faucet require replacement up to three times over a 10-year period. This module considers the impacts associated with the production and transportation of components required for product repair.

Module B4-B5: Replacement and refurbishment

These modules include anticipated replacement or refurbishment events during the reference service life associated with replacing a whole product (Module B4) and restoration of parts to a condition in which the products can perform its required function (Module B5). These modules are not applicable to sensor faucets as these products are not expected to be replaced as a whole product over a 10 year period. The replacement of certain worn out parts are considered as repair in Module B3.

Module B6: Operational Energy Use

This module is not applicable because the sensor faucet is battery operated and/or equipped with a solar panel to capture and store power. There is no primary energy consumption associated with these products.

Module B7: Operational Water Use

This module includes water use during the operation of the product (assumes a mix of 70% hot water and 30% cold water), together with its associated environmental aspects and impacts considering the life cycle of water which includes production, transportation and wastewater treatment. Impacts were calculated depending on the water use (gallons per minute) specifications of sensor faucets.

Module C1-C4: End-of-Life

The end-of-life stage of the product starts when it is replaced, dismantled or deconstructed from the building. Impacts for deconstruction and dismantling processes were not modeled in the LCA as it is a manual process with hand tools, and does not require any energy input for removal of the product. The impacts associated with transportation of waste materials to processing facilities, waste processing of material components and waste disposal of the product are included in these modules.

PROCESS FLOW DIAGRAM

The diagram below is a representation of the most significant contributions to the production for Basys® EFX sensor faucets. The following life cycle stages are included: production (Modules A1-A3); construction & installation (Module A4-A5); product use (Modules B1-B7); and end-of-life (Modules C1-C4).



LIFE CYCLE IMPACT ASSESSMENT

Life cycle impact assessment is the process of converting the life cycle inventory results into a representation of potential environmental and human health impacts. For example, emissions of carbon dioxide, methane, and nitrous oxide (inventory data) together contribute to climate change (impact assessment). The impact assessment for the EPD is conducted in accordance with the requirements of the Product Category Rule (PCR). Impact category indicators were estimated using TRACI v2.1 characterization method, including Global Warming Potential (100 year time horizon), Acidification Potential, Eutrophication Potential, Smog formation, Ozone Depletion Potential, and Fossil Fuel Depletion Potential.

Table 3. Results for 10 years of use of Basys® EFX sensor faucet.

Impact Category	Production			Construction & Installation		Use			End-of-Life			
	Raw Material Extraction/ Processing	Transport to the Manufacturer	Manufacturing	Transportation	Installation	Maintenance	Repair	Operational Water Use	Demolition	Transportation	Waste Processing	Disposal
	A1	A2	A3	A4	A5	B2	B3	B7	C1	C2	C3	C4
Ecological Indicators												
Acidification (kg SO ₂ eq)	0.27	2.5x10 ⁻³	1.7x10 ⁻³	7.9x10 ⁻³	2.4x10 ⁻⁵	5.1x10 ⁻²	3.2x10 ⁻³	See Table 4	0.0	9.9x10 ⁻⁶	8.4x10 ⁻⁴	4.4x10 ⁻⁴
Eutrophication (kg N eq)	0.42	5.9x10 ⁻⁴	4.5x10 ⁻⁴	1.4x10 ⁻³	5.1x10 ⁻⁴	2.1x10 ⁻²	4.7x10 ⁻³		0.0	2.4x10 ⁻⁶	7.1x10 ⁻⁴	5.1x10 ⁻³
Global Warming (kg CO ₂ eq)	14	0.54	0.25	1.2	0.08	8.3	0.21		0.0	2.1x10 ⁻³	0.22	0.54
Ozone Depletion (kg CFC-11 eq)	8.0x10 ⁻⁷	1.0x10 ⁻⁷	4.9x10 ⁻⁸	2.3x10 ⁻⁷	2.6x10 ⁻¹⁰	8.2x10 ⁻⁷	1.4x10 ⁻⁸		0.0	4.2x10 ⁻¹⁰	1.0x10 ⁻⁸	9.5x10 ⁻⁹
Human Health Indicators												
Smog (kg O ₃ eq)	1.4	5.8x10 ⁻²	6.0x10 ⁻³	0.16	3.9x10 ⁻⁴	0.50	1.7x10 ⁻²	See Table 4	0.0	2.3x10 ⁻⁴	9.8x10 ⁻³	6.9x10 ⁻³
Resource Depletion												
Fossil Fuel Depletion (MJ surplus)	13	1.2	0.54	2.7	3.4x10 ⁻³	29	0.20	See Table 4	0.0	4.9x10 ⁻³	0.15	0.11

The operational water use phase considers the volume of water required per minute (assumes a mix of 70% hot water and 30% cold water), the embedded energy required for water supply, distribution and wastewater treatment, and the number of uses over a 10-year period. The volume of water required per use (expressed in terms of gallons per minute) varies depending on the design specification of the sensor faucet.

Table 4. Results for Module B7: Operational Water Use scenarios for Basys® EFX sensor faucet (90 uses per day over 10 year period).

Impact Category	USE SCENARIO FOR B7: Operational Water Use	
	Basys® EFX Sensor Faucets (90 uses per day over 10 years)	
	0.5 gpm	
Ecological Indicators		
Acidification (kg SO ₂ eq)	5.7	
Eutrophication (kg N eq)	8.5	
Global Warming (kg CO ₂ eq)	1,100	
Ozone Depletion (kg CFC-11 eq)	1.4x10 ⁻⁴	
Human Health Indicators		
Smog (kg O ₃ eq)	31	
Resource Depletion		
Fossil Fuel Depletion (MJ surplus)	2,600	

ADDITIONAL ENVIRONMENTAL PARAMETERS

ISO 21930 requires that several parameters be reported in the EPD, including resource use, waste categories and output flows, and other environmental information. The results for these parameters are shown in Table 5 and Table 6.

Acronym	Parameter
RPR _E	Renewable primary resources used as an energy carrier (fuel)
RPM _E	Renewable primary resources with energy content used as material
NRPR _E	Non- renewable primary resources used as an energy carrier (fuel)
NRPM _E	Non- renewable primary resources with energy content used as material
SM	Secondary materials
RSF	Renewable secondary fuels
NRSF	Non- renewable secondary fuels
RE	Recovered energy
NHW	Non-hazardous waste disposed
HW	Hazardous waste disposed
RW	Radioactive waste disposed
CFR	Components for reuse
MFR	Materials for recycling
MER	Materials for energy recovery
EE _I	Exported energy from incineration
EE _L	Exported energy from landfill

Table 5. Results for 10 years of use of Basys® EFX sensor faucet by module. Results representing energy flows are calculated using lower heating (i.e., net calorific) values.

Environmental parameter	Production			Construction & Installation		Use			End-of-Life				
	Raw Material Extraction/ Processing	Transport to the Manufacturer	Manufacturing	Transportation	Installation	Maintenance	Repair	Operational Water Use	Demolition	Transportation	Waste Processing	Disposal	
	A1	A2	A3	A4	A5	B2	B3	B7	C1	C2	C3	C4	
RPR _E (MJ)	22	0.13	1.3	0.30	1.8x10 ⁻³	6.2	0.29	See Table 6	0.0	4.2x10 ⁻⁴	0.2	0.12	
RPM _E (MJ)	9.9x10 ⁻⁴	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	0.0
NRPR _E (MJ)	179	9.1	9.7	20	3.5x10 ⁻²	240	2.8		0.0	3.1x10 ⁻²	1.5	1.6	
NRPM _E (MJ)	4.4	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	
SM (MJ)	0.087	0.0	0.027	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	
RSF (MJ)	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	
NRSF (MJ)	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	
RE (MJ)	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	
Water Use (m ³)	2.4	3.5x10 ⁻³	2.0x10 ⁻³	2.9x10 ⁻²	5.4x10 ⁻⁵	1.0	0.11		0.0	2.3x10 ⁻⁵	5.3x10 ⁻³	4.2x10 ⁻³	
NHW (kg)	3.3	0.73	7.6x10 ⁻³	1.5	6.8x10 ⁻²	0.48	4.5x10 ⁻²		0.0	2.5x10 ⁻³	5.1x10 ⁻²	0.60	
HW (kg)	1.7x10 ⁻³	4.5x10 ⁻⁶	2.5x10 ⁻⁶	1.0x10 ⁻⁵	3.5x10 ⁻⁸	1.0x10 ⁻⁴	1.2x10 ⁻⁴		0.0	1.5x10 ⁻⁸	4.5x10 ⁻³	3.1x10 ⁻⁶	
RW (kg)	5.9x10 ⁻⁵	9.8x10 ⁻⁶	1.3x10 ⁻⁵	2.2x10 ⁻⁵	1.7x10 ⁻⁸	3.2x10 ⁻⁵	9.5x10 ⁻⁷		0.0	3.3x10 ⁻⁸	8.1x10 ⁻⁷	1.4x10 ⁻⁶	
CFR (kg)	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	
MFR (kg)	0.0	0.0	0.0	0.0	0.17	0.0	0.0		0.0	0.0	0.47	0.0	
MER (kg)	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	
EE, Total (MJ)	0.0	0.0	0.0	0.0	0.30	0.0	0.0		0.0	0.0	0.0	0.028	
EE _v , Electricity (MJ)	0.0	0.0	0.0	0.0	0.066	0.0	0.0		0.0	0.0	0.0	9.4x10 ⁻³	
EE _i , Heat (MJ)	0.0	0.0	0.0	0.0	0.13	0.0	0.0		0.0	0.0	0.0	0.019	
EE _L , Electricity (MJ)	0.0	0.0	0.0	0.0	0.10	0.0	0.0		0.0	0.0	4.2x10 ⁻⁴	0.2	0.12
EE _L , Heat (MJ)	0.0	0.0	0.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	0.0
Biogenic CO ₂ (kg CO ₂)	-4.2x10 ⁻⁵	0.0	-0.58	0.0	0.21	0.0	0.0	0.0	0.0	3.1x10 ⁻²	1.5	1.6	

Table 6. Results for scenarios for Module B7: Operational Water Use scenarios Basys® EFX sensor faucet (90 uses per day over 10 year period). Results representing energy flows are calculated using lower heating (i.e., net calorific) values.

Environmental Parameter	USE SCENARIO FOR B7: Operational Water Use
	Basys® EFX Sensor Faucets (90 uses per day over 10 years)
	0.5 gpm
RPR _E (MJ)	1,500
RPM _E (MJ)	0.0
NRPR _E (MJ)	29,600
NRPM _E (MJ)	0.0
SM (MJ)	0.0
RSF (MJ)	0.0
NRSF (MJ)	0.0
RE (MJ)	0.0
Water Use (m ³)	80
NHW (kg)	39
HW (kg)	3.6x10 ⁻²
RW (kg)	1.2x10 ⁻²
CFR (kg)	0.0
MFR (kg)	0.0
MER (kg)	0.0
EE, Total (MJ)	0.0
EE _i , Electricity (MJ)	0.0
EE _i , Heat (MJ)	0.0
EE _L , Electricity (MJ)	0.0
EE _L , Heat (MJ)	0.0
Biogenic CO ₂ (kg CO ₂)	0.0

Interpretation of Results

Overall, the Basys® EFX sensor faucet production and assembly operations occurring at the Swiss facility (Module A3) has negligible impacts across all the impact category indicators. The major hotspot in the supply chain lies in the operational water use (Module B7), accounting for 95-99% of total impacts across all impact categories. The raw material extraction and processing (Module A1), which primarily includes the production of zamak and brass components has a small contribution across the supply chain of the Basys® EFX sensor faucet production. The impacts associated with use phase are mainly because of the energy required to heat water (water use is a mix of 70% hot water/30% cold water) and the embedded energy in water supply, distribution and wastewater treatment. As such, the operational water use data used for Module B7 has a significant influence on the final results depending on the number of assumed uses and the water delivered per use (gallons per minute).

SUPPORTING TECHNICAL INFORMATION

Data Sources. Data sources used for the LCA. Materials less than 1% of product mass are not listed.

Material	Dataset	Publication Date
Product		
ABS	Acrylonitrile-butadiene-styrene copolymer {GLO} market for Alloc Rec, U ¹ ; Injection moulding {GLO} market for Alloc Rec, U ¹	2016
Brass components	Brass {GLO} market for Alloc Rec, U ¹	2016
Acetal	Polypropylene, granulate {GLO} market for Alloc Rec, U ¹ ; Injection moulding {GLO} market for Alloc Rec, ¹	2016
Copper	Copper {GLO} average, no market transport Alloc Rec, U ¹ ; Metal working, average for copper product manufacturing {RoW} processing Alloc Rec, U ¹	2016
EPDM	Synthetic rubber {GLO} market for Alloc Rec, U ¹	2016
Battery	Battery cell, Li-ion {GLO} market for Alloc Rec, U ¹	2016
LDPE	Polyethylene, low density, granulate {RoW} production Alloc Rec, U ¹ ; Injection moulding {GLO} market for	2016
Nylon 6-glass filled	Nylon 6, glass-filled {RoW} production Alloc Rec, U ¹ ; Injection moulding {GLO} market for Alloc Rec, U ¹	2016
PPA, 40% GF	Polypropylene, granulate {RoW} production Alloc Rec, U ¹ ; Glass fibre {RoW} production Alloc Rec, U ¹	2016
Rubber	Literature ³	2016
Polypropylene	Polypropylene, granulate {RoW} production Alloc Rec, U ¹ ; Injection moulding {GLO} market for Alloc Rec, ¹	2016
Solar panel	Photovoltaic panel, a-Si {US} production Alloc Rec, U ¹	2016
Stainless steel	Steel, chromium steel 18/8, hot rolled {GLO} market for Alloc Rec, U ¹	2016
PVC	Polyvinylchloride, suspension polymerised {GLO} average, no market transport Alloc Rec, U ¹ ; Injection moulding {GLO} market for Alloc Rec, U ¹	2016
Zamak	Zamak ³ {GLO} market for Alloc Rec ^{1,2}	2016
Sensor	Neodymium oxide {GLO} average, no market transport Alloc Rec, U, Bronze {RoW} production Alloc Rec, U, Glass fibre reinforced plastic, polyamide, injection moulded {RoW} production Alloc Rec, U, Silica fume, densified {GLO} silica fume, densified, Recycled Content cut-off Alloc Rec, U, Bronze {RoW} production Alloc Rec, U, Copper {GLO} average, no market transport Alloc Rec, U, Zinc {GLO} primary production from concentrate Alloc Rec, U, Polyvinylchloride, suspension polymerised {GLO} average, no market transport Alloc Rec, U ¹	2016
Packaging		
Plastic film	Packaging film, low density polyethylene {GLO} market for Alloc Def, U ¹	2016
Corrugated box	Corrugated board box {RoW} production Alloc Rec, U ¹	2016
Paper	Kraft paper, bleached {RER} production Alloc Rec, U ¹	2016
Label	Printing ink, offset, without solvent, in 47.5% solution state {RER} printing ink production, offset, product in 47.5% solution state Alloc Rec, U ¹ ; Packaging film, low density polyethylene {GLO} market for Alloc Def, U ¹	2016
Maintenance		
Sodium lauryl sulfate	Fatty alcohol sulfate {RoW} production, petrochemical Alloc Rec, U ¹	2016
Water	Tap water {RoW} market for Alloc Rec, U ¹	
Resource Use		
Electricity	Electricity, medium voltage {CH} Alloc Rec, U ¹	2016
Water use	Electricity, medium voltage {US} market group for Alloc Rec, U ¹	2016
Natural Gas	Heat, district or industrial, natural gas {GLO} market group for Alloc Rec, U ¹	2016

¹Ecoinvent 3.3 Life Cycle Database; ²Jawjit, W., et al., (2009); ³SCS Global Services

Data Quality

Data Quality Parameter	Data Quality Discussion
Time-Related Coverage: Age of data and the minimum length of time over which data is collected	Manufacturer provided primary data on product manufacturing for the Swiss facility based on annual production for 2017, respectively. Representative datasets (secondary data) used for upstream and background processes are generally less than 10 years old from original publication, but almost all have been updated in the last two years.
Geographical Coverage: Geographical area from which data for unit processes is collected to satisfy the goal of the study	The data used in the analysis is considered to be of high quality and provide the best possible representation available with current data. Datasets used in the assessment are representative of the US, Global, and "Rest-of-World" (average for all countries in the world with uncertainty adjusted). Datasets chosen are considered sufficiently similar to actual processes and are of good data quality.
Technology Coverage: Specific technology or technology mix	Data are representative of the actual technologies used for processing, transportation, and manufacturing operations. Data was collected for all key processes including faucet production and assembly, packaging and transportation.
Precision: Measure of the variability of the data values for each data expressed	Precision of results are not quantified due to a lack of data. Data collected for operations were typically averaged for one or more years and over multiple operations, which is expected to reduce the variability of results.
Completeness: Percentage of flow that is measured or estimated	The LCA model included all known mass and energy flows for production of sensor faucets. No known processes or activities contributing to more than 1% of the total environmental impact for each indicator are excluded.
Representativeness: Qualitative assessment of the degree to which the data set reflects the true population of interest	Overall, data used in the assessment represent actual processes for production of sensor faucets. Primary data is used to model manufacture of sensor faucets. Data is considered to be representative of the actual technologies used for faucet production.
Consistency: Qualitative assessment of whether the study methodology is applied uniformly to the various components of the analysis	The consistency of the assessment is considered to be high. Data sources of similar quality and age are used, with a bias towards Ecoinvent data.
Reproducibility: Qualitative assessment of the extent to which information about the methodology and data values would allow an independent practitioner to reproduce the results reported in the study	Based on the description of data and assumptions used, this assessment would be reproducible by other practitioners. All assumptions, models, and data sources are documented.
Sources of the Data: Description of all primary and secondary data sources	Data representing energy use at the manufacturer's facilities represent an annual average. Primary data were available for all key processes across the supply chain including faucet production and assembly, packaging, transportation for sensor faucets. LCI datasets from Ecoinvent were used to model all unit processes.
Uncertainty of the Information: Uncertainty related to data, models, and assumptions	Uncertainty related to the product materials and packaging is low. The secondary datasets are considered to be representative as primary data was collected from the Sloan production facilities. Uncertainty related to the impact assessment methods used in the study is relatively high. The impact assessment method required by the PCR includes impact potentials, which lack characterization of providing and receiving environments or tipping points.

REFERENCES

1. Ecoinvent Centre (2016) Ecoinvent data from v3.3. Swiss Center for Life Cycle Inventories, Dübendorf, 2016, <http://www.ecoinvent.org>
2. SM Transparency Report Framework: Part A: LCA Calculation Rules and Background Report Requirements version 2018. Part B: Commercial Lavatory Faucet Product Group; Sustainable Minds (July 3, 2018).
3. ISO 14025: 2006 Environmental labels and declarations – Type III environmental declarations – Principles and Procedures.
4. ISO 14040: 2006 Environmental Management – Life cycle assessment – Principles and framework.
5. ISO 14044: 2006 Environmental Management – Life cycle assessment – Requirements and Guidelines.
6. ISO 21930: 2017 Sustainability in building construction – Environmental declaration of building products.
7. Jawjit,W., et al., Greenhouse gas emissions from rubber industry in Thailand, J Clean Prod (2010), doi:10.1016/j.jclepro.2009.12.003
8. LEEDv4 Reference Guide. Indoor Water Use Reduction credit calculation. U.S. Green Building Council. 2013.
9. Life Cycle Assessment of Basys® EFX, Optima® EBF and Basys® EFX Faucets. Prepared for Sloan Valve Company. SCS Global Services. September 2018.
10. SCS Type III Environmental Declaration Program: Program Operator Manual v10.0. April 2019. SCS Global Services.
11. SimaPro software (version 8.3): <https://www.pre-sustainability.com/simapro>
12. Tool for the Reduction and Assessment of Chemical and Other Environmental Impacts (TRACI). Version 2.1. US Environmental Protection Agency.
13. US EPA. Advancing Sustainable Materials Management: 2013 Fact Sheet. Assessing Trends in Material Generation, Recycling and Disposal in the United States. June 2015.
14. US EPA. WARM Model Transportation Research - Draft. Memorandum from ICF Consulting to United States Environmental Protection Agency. September 7, 2004. <http://epa.gov/epawaste/conserve/tools/warm/SWMMGHGreport.html#background>.
15. Plumbing Manufacturers International (PMI), Product Category Rule (PCR) Guidance for Kitchen and Bath Fixture Fittings <https://www.safeplumbing.org/files/safeplumbing.org/documents/resources/PMI-Kitchen-and-Bath-Fixture-Fitting-PCR-Guidance-Document.pdf>.





For more information contact:

Sloan Valve Company

10500 Seymour Avenue, Franklin Park, IL 60131
P: 847.671.4300 | 800.982.5839 | www.sloan.com



SCS Global Services

2000 Powell Street, Ste. 600, Emeryville, CA 94608 USA
Main +1.50.452.8000 | fax +1.510.452.8001